

**SUBPART I - Standards of Performance for Asphalt Concrete Plants**  
(Delegation Effective 11-8-76)

**RULE 260.90. APPLICABILITY AND DESIGNATION OF AFFECTED FACILITY** (Rev. Effective: 1-13-87)

The affected facility to which the provisions of this subpart apply is each hot mix asphalt facility which commenced construction, reconstruction, or modification after June 11, 1973. For the purpose of this subpart, a hot mix asphalt facility is comprised only of any combination of the following: dryers; systems for screening, handling, storing, and weighing hot aggregate; systems for loading, transferring, and storing mineral filler; systems for mixing hot asphalt concrete; and the loading, transfer, and storage systems associated with emission control systems.

**RULE 260.91. DEFINITIONS**

As used in this subpart, all terms not defined herein shall have the meaning given them in Subpart A of this regulation.

(a) **"Hot Mix Asphalt Facility"** means any facility, as described in Rule 260.90, used to manufacture hot mix asphalt by heating and drying aggregate and mixing with asphalt cements.

**RULE 260.92. STANDARD FOR PARTICULATE MATTER**

(a) On and after the date on which the performance test required to be conducted by Rule 260.8 is completed, no owner or operator subject to the provisions of this subpart shall discharge into the atmosphere from any affected facility any gases which:

- (1) Contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).
- (2) Exhibit 20 percent opacity, or greater.

**RULE 260.93. TEST METHODS AND PROCEDURES**

Performance tests shall be conducted as specified in Part 60, Chapter I, Title 40, Code of Federal Regulations, Section 60.93.