

MONTH: _____

YEAR: _____

**DAILY OPERATIONS AND MAINTENANCE CHECKLIST
SAN DIEGO COUNTY AIR POLLUTION CONTROL DISTRICT
17 CCR, §93109: DRY CLEANING OPERATIONS USING PERCHLOROETHYLENE**

BUSINESS NAME & ADDRESS: _____

Component	ATCM Requirement	Week of _____						
		Mon.	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.
Refrigerated Vapor Condenser	Vapor air outlet temperature must be at or below 45 °F or 7 °C during cool down (record temperature).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers (please check).							

Component	ATCM Requirement	Week of _____						
		Mon.	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.
Refrigerated Vapor Condenser	Vapor air outlet temperature must be at or below 45 °F or 7 °C during cool down (record temperature).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers (please check).							

Component	ATCM Requirement	Week of _____						
		Mon.	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.
Refrigerated Vapor Condenser	Vapor air outlet temperature must be at or below 45 °F or 7 °C during cool down (record temperature).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers (please check).							

Component	ATCM Requirement	Week of _____						
		Mon.	Tues.	Wed.	Thur.	Fri.	Sat.	Sun.
Refrigerated Vapor Condenser	Vapor air outlet temperature must be at or below 45 °F or 7 °C during cool down (record temperature).							
Button and Lint Traps	Clean traps every day and place lint in tightly sealed containers (please check).							

The refrigerated condenser shall have a graduated or digital thermometer with a minimum range from 0° F (-18° C) to 150° F (66° C) which measures the temperature of the outlet vapor stream, downstream of any bypass of the condenser, and is easily visible to the operator. A spare lint filter and a spare set of gaskets for the loading door, still, lint trap, button trap, and water separator shall be kept on site.