

F01 - Polyester Resin & Fiberglass Ops, Hand Lay Up, Clean Up Solvent, Uncontrolled

CALCULATION METHODS

$$E_a = U_a \text{ (gal/yr)} \times D \text{ (lbs/gal)} \times \text{Conc. (lbs/lb)} \times \text{MEF} \times (1 - e)$$

$$E_h = U_h \text{ (gal/hr)} \times D \text{ (lbs/gal)} \times \text{Conc. (lbs/lb)} \times \text{MEF} \times (1 - e)$$

NOTES:

- Assume no monomers are present in the clean up solvent (i.e . monomer emission rate = 1.0).
- Nonvolatile compounds are assumed to have no emissions.
- All volatile organic solvent components used in the clean up are assumed to be fully released.
- Emission calculations are uncontrolled. Capture and removal efficiencies must be identified for controlled processes.

POLLUTANT	AP-42 Default Composition	EPA REFERENCE	EPA	(UNITS)	COMMENTS
	(weight percent)	DOCUMENT	FACTOR		
NOX					
CO					
SOX					
TOG	100.00				Assume TOG = sum of all solvents
ROG	100 - exempts				Assume ROG = TOG - Exempts
TSP					
PM10					
ACETONE					
METHYL METHACRYLATE		Section 4.4 AP-42 (1/95)			- Assume no monomers are present in the clean up solvent (i.e . monomer emission rate = 1.0).
STYRENE		Section 4.4 AP-42 (1/95)			- Assume no monomers are present in the clean up solvent (i.e . monomer emission rate = 1.0).
TOLUENE					
XYLENES					