M10 - METAL DEPOSITION, FLAME SPRAY, SCRUBBER, DEFAULT FACTORS

CALCULATION METHODS

Ea = Ua x Ci (lbs metal / lb material sprayed) x EF (lbs released/lb metal sprayed)

Eh = Uh x Ci (lbs metal / lb material sprayed) x EF (lbs released/lb metal sprayed)

NOTES:

- Annual (Ua) and maximum hourly (Uh) throughputs must be individually reported for each material sprayed.
- Emission factors are in units of (lbs individual metal released / lb individual metal sprayed) after controls.
- Site specific emission factors should be used where available.
- Default emission factors have been developed from the limitted site specific data collected to date. These values will be updated as additional information is generated.
- Combustion related emissions of NOx, CO, SOx, PIC's, etc. are assumed to be negligible as no emissions information currently exists.

- Only very limited data regarding the conversion rate of chromium to hexavalent chromium exists. At this time, source test results are used for Cr+6 in lieu of a more standard approach.

POLLUTANT	District Emission Factor	REFERENCE	TEST	(UNITS)	COMMENTS
	(lbs/lb emissions)	DOCUMENT	LOCATION		
NOX					
CO					
SOX					
TOG					
ROG					
TSP		ave. of Cr+6 & Cr test results	NAS N Island	lbs/lb material sprayed	Base this estimate on overall usage (lbs of material)
PM10	4.67E-03	ave. of Cr+6 & Cr test results	NAS N Island	lbs/lb material sprayed	Base this estimate on overall usage (lbs of material)
ALUMINUM					
ARSENIC					
BARIUM					
BERYLLIUM					
CADMIUM					
CHROMIUM HEXAVALENT	4.67E-03	Site Specific test result			
CHROMIUM NONHEXAVALENT	4.67E-05	Site Specific test result			Test result was 99% hexavalent chromium.
NICKEL	4.67E-03	Site Specific test result			
* OTHER LISTED METALS *	4.67E-03	Average of Ni & Cr test results			Assume other metals released at a rate equal to the average of the Cr+6 & Cr (total) values.
ZINC					

Last Updated on 8/24/99 By A. dela Cruz