## S125 - 9018, Shielded Metal Arc Welding (SMAW) Welding Process Emission Factors

S125 - 9018, Shielded Metal Arc Welding (SMAW) Welding Process Emission Factors								
CALCULATION METHODS	<u>.</u>							
Annual Emissions: Ea = Ua x E Hourly Emissions: Eh = Uh x E	F (lbs/lb rod) x (1-e)							
Ea = Annual emissions of each listed toxic air contaminant per welding rod, (lbs/year) Eh = Maximum hourly emissions of each listed toxic air contaminant per welding rod, (lbs/hour) Ua = Annual usage of each welding rod, (lbs/year) Uh = Maximum hourly usage of each welding rod, (lbs/hour) EF = Emission Factor (lbs/lb rod)								
<ul> <li>(2) Incomplete AP-42 Final Sec</li> <li>(3) No AP-42 information but k</li> <li>(4) District Study or AWMA in:</li> <li>(5) Incomplete District Study in</li> </ul>	tion 12.19 (1/95): EF = FGF nown welding process: EF = formation: EF = Trace Meta formation: EF = FGR (Distr		) MSDS)	Fumes) EF x H0	CR			
<ul> <li>NOTES:</li> <li>Emission factors assume "uncontrolled" releases. Emission control methods and efficiencies reported are be applied within the emission calculations.</li> <li>Fume generation rates (FGR) are based on the following: <ul> <li>olEPA AP-42 Final Section 12.19 (1/95) Table 12.19-1 (PM10 EF)</li> <li>olARB, Richard Bode: 0.01 (GMAW, TIG, MIG), 0.02 (SMAW, FCAW), 0.00005 (SAW), 0.05 (unspecified)</li> </ul> </li> <li>Fume Correction Factors (FCF) per District engineering discussions with Industry: <ul> <li>ol0.5464 (GMAW, TIG, MIG), 0.2865 (SMAW, FCAW, SAW), 1.0 (unspecified)</li> </ul> </li> <li>Trace metal emission factors are based on the following: <ul> <li>olAWMA Volume 59, 2009, Issue 5 (Pages 619-626) Table 2 and Table 3</li> <li>olEPA AP-42 Final Section 12.19 (1/95) Table 12.19-2</li> <li>olDistrict engineering estimates using rod compositions (Ci) from MSDS</li> </ul> </li> <li>Hexavalent chromium conversion rates (HCR) are per District engineering reviews of studies on welding: <ul> <li>ol.05 (GMAW, TIG, MIG), 0.55 (SMAW), 0.0005 (SAW), 0.10 (FCAW, unspecified)</li> </ul> </li> </ul>								
POLLUTANT	DISTRICT EMISSION FACTORS (lbs/lb rod)	REFERENCE DOCUMENT	FACTOR	(UNITS)	COMMENTS			
NOX								
СО								
SOX								
TOG								
VOC								
TSP	1.69E-02				Assume PM10 = TSP			
PM10	1.69E-02	EPA Table 12.19-1 (1/95) AP-42	16.9	lb/1000 lbs rod	Assume PM10 = Fume Generation Rate (FGR)			
AI								
Al2O3								
Ве								
Cd								

Со					
Cr	2.12E-04	EPA Table 12.19-2 (1/95) AP-42	2.12	0.1 lb/1000 lbs rod	District Procedure (1) EF = Trace Metal EF
Cr(VI)	1.17E-04	AWMA Page 623	55	%	District Procedure (*) EF = Cr EF x HCR
Cu					
Mn	7.83E-04	EPA Table 12.19-2 (1/95) AP-42	7.83	0.1 lb/1000 lbs rod	District Procedure (1) EF = Trace Metal EF
Ni	1.30E-05	EPA Table 12.19-2 (1/95) AP-42	0.13	0.1 lb/1000 lbs rod	District Procedure (1) EF = Trace Metal EF
Р					
Pb					
Crystalline Silica					
v					
Zn					
EFERENCES: PA AP-42 Chapter 12.19: https WMA: https://www.tandfonlir		oduction/files/2020-11/documents/c12 '1047-3289.59.5.619	s19.pdf		

Last Updated on 07/07/2022 by A.Weller