

S80 - Eni-CI, Shielded Metal Arc Welding (SMAW) Welding Process Emission Factors

CALCULATION METHODS

Annual Emissions: $E_a = U_a \times EF \text{ (lbs/lb rod)} \times (1-e)$

Hourly Emissions: $E_h = U_h \times EF \text{ (lbs/lb rod)} \times (1-e)$

E_a = Annual emissions of each listed toxic air contaminant per welding rod, (lbs/year)

E_h = Maximum hourly emissions of each listed toxic air contaminant per welding rod, (lbs/hour)

U_a = Annual usage of each welding rod, (lbs/year)

U_h = Maximum hourly usage of each welding rod, (lbs/hour)

EF = Emission Factor (lbs/lb rod)

Emission Factors:

(1) Complete AP-42 information from Final Section 12.19 (1/95) : $EF = \text{Trace Metal EF (Table 12.19-2)}$

(2) Incomplete AP-42 Final Section 12.19 (1/95) : $EF = FGR \text{ (Table 12.19-1)} \times FCF \times C_i$

(3) No AP-42 information but known welding process: $EF = FGR \text{ (District)} \times FCF \times C_i$

(4) Total Chromium and Hexavalent Chromium from AWMA: $EF = Cr/Cr+6 \text{ EF}$

(* Incomplete AP-42 or AWMA Hexavalent Chromium information: $EF = Cr \text{ (Total Chromium in Fumes)} \text{ EF} \times HCR$

NOTES:

- Emission factors assume "uncontrolled" releases. Emission control methods and efficiencies reported are be applied within the emission calculations.
- Fume generation rates (FGR) are based on the following:
 - EPA AP-42 Final Section 12.19 (1/95) Table 12.19-1 (PM10 EF)
 - ARB, Richard Bode: 0.01 (GMAW, TIG, MIG), 0.02 (SMAW, FCAW), 0.00005 (SAW), 0.05 (unspecified)
- Fume Correction Factors (FCF) per District engineering discussions with Industry:
 - 0.5464 (GMAW, TIG, MIG), 0.2865 (SMAW, FCAW, SAW), 1.0 (unspecified)
- Trace metal emission factors are based on the following:
 - AWMA Volume 59, 2009, Issue 5 (Pages 619-626) Table 2 and Table 3
 - EPA AP-42 Final Section 12.19 (1/95) Table 12.19-2
 - District engineering estimates using rod compositions (C_i) from MSDS
- Hexavalent chromium conversion rates (HCR) are per District engineering reviews of studies on welding:
 - 0.05 (GMAW, TIG, MIG), 0.55 (SMAW), 0.0005 (SAW), 0.10 (FCAW, unspecified)

POLLUTANT	DISTRICT EMISSION FACTORS (lbs/lb rod)	REFERENCE DOCUMENT	FACTOR	(UNITS)	COMMENTS
NOX					
CO					
SOX					
TOG					
VOC					
TSP	1.82E-02				Assume PM10 = TSP
PM10	1.82E-02	EPA Table 12.19-1 (1/95) AP-42	18.2	lb/1000 lbs rod	Assume PM10 = Fume Generation Rate (FGR)
Cr					
Cr(VI)					

POLLUTANT	DISTRICT EMISSION FACTORS (lbs/lb rod)	REFERENCE DOCUMENT	FACTOR	(UNITS)	COMMENTS
Co					
Mn	3.90E-05	EPA Table 12.19-2 (1/95) AP-42	0.39	.1 lb/1000 lbs rod	District Procedure (1) EF = Trace Metal EF
Ni	8.90E-04	EPA Table 12.19-2 (1/95) AP-42	8.9	.1 lb/1000 lbs rod	District Procedure (1) EF = Trace Metal EF
Pb					
Cu					
REFERENCES:					
EPA AP-42 Chapter 12.19: https://www.epa.gov/sites/production/files/2020-11/documents/c12s19.pdf					
AWMA: https://www.tandfonline.com/doi/abs/10.3155/1047-3289.59.5.619					

Last Updated on 02/23/2022 by A.Weller