

---

---

**San Diego County Air Pollution Control District**

10124 Old Grove Road  
San Diego, CA 92131-1649  
(858) 586-2600

---

---

**TITLE V OPERATING PERMIT**  
**# APCD2008-TVP-971226**

**Issued To:**

Sycamore Landfill Inc.  
Site ID # APCD1989-SITE-03596

**Site Address**

8514 Mast Blvd.  
Santee, CA 92071  
(619) 449-9156

**Mailing Address**

8514 Mast Blvd.  
Santee, CA 92071

**Responsible Official:** Neil Mohr; Alternate – Jesus Torres  
**Facility Contact:** Jordy Bjorkman  
**Permit Information Contact:** Holly Aasen

---

Issued by the San Diego County Air Pollution Control District on: \_\_\_\_\_

This Title V Operating Permit expires on: \_\_\_\_\_

Signed by: \_\_\_\_\_

PAULA A. FORBIS, Air Pollution Control Officer

Date: \_\_\_\_\_

## TABLE OF CONTENTS

	<b>PAGE</b>
<b>PREAMBLE</b>	<b>1</b>
<b>SECTION I. REGULATION XIV PERMIT REQUIREMENTS</b>	<b>2</b>
A. ADMINISTRATIVE PERMIT TERMS	2
B. RENEWAL REQUIREMENTS AND TERMS	2
C. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS	3
D. GENERAL PERMIT REQUIREMENTS	4
<b>SECTION II. FACILITY-WIDE REQUIREMENTS</b>	<b>5</b>
A. GENERAL PERMIT PROGRAM APPLICABLE REQUIREMENTS	5
B. FACILITY-WIDE/OTHER PROHIBITORY & MISC. REQUIREMENTS	5
C. PERMIT SHIELDS	6
D. ADDITIONAL TERMS	6
<b>SECTION III. EMISSION UNIT REQUIREMENTS</b>	<b>6</b>
A. DISTRICT PERMITTED EMISSION UNITS	6
B. REGISTERED AND LEASED EMISSION UNITS	6
C. INSIGNIFICANT EMISSION UNITS AND ACTIVITIES	7
D. ENGINES SUBJECT TO THE FEDERAL NESHAP	7
<b>SECTION IV. DISTRICT ONLY PROVISIONS</b>	<b>7</b>
A. VARIANCE PROCEDURES	7
<b>SECTION V. APPENDICES</b>	<b>A-1</b>
A. DISTRICT PERMITS AND REGISTERED UNITS	A-1
B. RULE REFERENCE TABLE	B-1
C. ABBREVIATIONS	C-1

## PREAMBLE

This Title V Operating Permit consists of this document and all appendices, including District permits incorporated by reference. The facility is subject to all applicable requirements identified within this permit, unless a specific permit shield is specified within this permit. If an applicable requirement is omitted from this permit, the facility is still obligated to comply with such an applicable requirement. The permittee must comply with all of the terms listed in each section of this permit.

This permit contains five major sections: Section I contains the Regulation XIV requirements required to carry out the Title V Operating Permit program. Section II contains the requirements that are applicable to the facility on a facility-wide basis. Section III contains the requirements that are applicable to individual emission units which have been issued District permits or District registration, or which have been determined to be insignificant emission units. Section IV contains terms and requirements pertaining to variance procedures and compliance schedules, if applicable to the facility. Section V contains three appendices. Appendix A contains all the District permits incorporated within this permit. Appendix B contains a table of all SIP approved and District approved rules. Appendix C contains a list of abbreviations used within this permit.

Copies of the Rules and Regulations of the Air Pollution Control District of San Diego County and the Rules and Regulations for San Diego County contained in the State Implementation Plan (SIP) approved by EPA may be obtained at the District. Copies are also available for review at the following locations:

SD Air Pollution Control District (Library & Public Review Area)	County of SD Law Library (Downtown)	County of SD Law Library (North County)
10124 Old Grove Road San Diego, CA 92131-1649 (858) 586-2600	1105 Front Street San Diego, CA 92101 (619) 531-3900	325 S. Melrose Dr., Suite 300 Vista, CA 92083 (760) 940-4386

The current Rules and Regulations of the Air Pollution Control District of San Diego County may also be viewed and downloaded using the following internet address:

[www.sdapcd.org](http://www.sdapcd.org)

The following addresses should be used to submit any certifications, reports or other information required by this permit:

SD Air Pollution Control District Compliance Division 10124 Old Grove Road San Diego, CA 92131-1649	USEPA Region IX Director of the Air Division Attn: Air-3 75 Hawthorne Street San Francisco, CA 94105
--	---

## **SECTION I. REGULATION XIV PERMIT REQUIREMENTS**

### **A. ADMINISTRATION PERMIT TERMS**

1. This Title V Operating Permit expires 5 years from date of issuance. [Rule 1410]
2. Commencing or continuing operation under this permit to operate shall be deemed acceptance of all terms and conditions specified within this permit. This does not limit the right of the applicant to seek judicial review or seek federal EPA review of a permit term or condition. [Rule 1421]
3. This permit may be modified, revoked, reopened and reissued, or terminated by the District for cause. [Rule 1421]
4. The filing of a request by the facility for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay the applicability of any permit condition. [Rule 1421]
5. This permit does not convey any property rights of any sort, or any exclusive privilege. [Rule 1421]
6. The need for the permittee to halt or reduce a permitted activity in order to maintain compliance with any term or condition of this permit shall not be a defense for any enforcement action brought as a result of a violation of any such term or condition. [Rule 1421]
7. In the event of challenge to any portion of this permit, the rest of the permit remains valid. [Rule 1421]
8. For the purpose of submitting compliance certifications or establishing whether or not a person has violated or is in violation of any applicable requirement in this permit, nothing in this permit shall preclude the use, including the exclusive use, of any credible evidence or information, relevant to whether a source would have been in compliance with applicable requirements if the appropriate performance or compliance test or procedure had been performed. [Rule 1421]

### **B. RENEWAL REQUIREMENTS AND TERMS**

1. The permittee shall submit a complete application for renewal of this permit to the Air Pollution Control Officer at least 12 months, but not more than 18 months, prior to permit expiration. [Rule 1410]
2. If an administratively complete application for renewal of this permit has been submitted to the Air Pollution Control Officer within the timeframe specified in Section I.B.1. , the terms and conditions of this permit shall remain in effect and the source may continue operations under these terms and conditions until the Air Pollution Control Officer issues or denies the permit renewal. [Rule 1410]

### **C. MONITORING, RECORDKEEPING & REPORTING REQUIREMENTS**

The permittee shall provide the District access to the facility and all equipment subject to this permit, and access to all required records pursuant to California Health and Safety Code Section 41510. [Rule 1421]

2. The permittee shall maintain all records required by this permit including any calibration, maintenance, and other supporting information and copies of all reports required by this permit for at least five (5) years from their date of creation. Such records shall be maintained on-site for a minimum of three years. This requirement controls and supersedes any other record retention requirement under this permit as it pertains to, and is required by, District Rule 1421 and Title V of the Clean Air Act. [Rule 1421]
3. Records required by this permit shall be considered as being maintained "on-site" if records for the previous 12-month period are available at the stationary source and any additional records are maintained at a location to be specified by the source and made readily available to the District upon request. [Rule 21]
4. The permittee shall submit monitoring and recordkeeping summary reports and all other monitoring and recordkeeping reports required by this permit to the District every six months, unless a shorter time frame is required by a specific permit condition contained in Section III of this permit. Unless other dates are specified in Section III, reports for data required to be collected from January 1 through June 30, shall be submitted no later than September 1 of the calendar year, and reports for data required to be collected from July 1 through December 31, shall be submitted no later than March 1 of the following calendar year. The report for the final six months of the year may be consolidated with the annual compliance certification required below. All instances of noncompliance from federally enforceable applicable requirements shall be clearly identified in these reports. (Timely completion of District Certification Reports Form 1401-J1 and Form 1401-J2, if applicable, and all indicated attachments, fulfills the requirements of this condition.) [Rule 1421]
5. Each calendar year, the permittee shall submit to the District and to the federal EPA an annual compliance certification, in a manner and form approved in writing by the District, for the previous calendar year that includes the identification of each applicable term or condition of the final permit for which the compliance status is being certified, the compliance status and whether the facility was in continuous or intermittent compliance during the previous calendar year, identification of the method used to determine compliance during the previous calendar year, and any other information required by the District to determine the compliance status. The annual compliance certification for a calendar year shall be submitted no later than March 1 of the following calendar year and may be consolidated with the monitoring and recordkeeping report for the last six months of the year for which compliance is certified. (Timely completion of District Certification Reports Form 1401-J1 and Form 1401-J2, if applicable, and all indicated attachments, fulfills the requirements of this condition.) [Rule 1421]
6. Any report submitted to the District or federal EPA pursuant to this permit to comply with a federally enforceable applicable requirement, shall be certified by a responsible official stating that, based on information and belief formed after reasonable inquiry, the report is true, accurate and complete. [Rule 1421]

7. The permittee shall make any trade secret designations of records, documents, or other information submitted to the District or federal EPA in accordance with District Rule 176. [Rule 176]
8. The permittee shall report all deviations from any and all federally enforceable permit terms and conditions including: (a) breakdowns, whether or not they result in excess emissions, (b) deviations that result in excess emissions of any regulated air pollutant, and (c) deviations from monitoring, recordkeeping, reporting and other administrative requirements that do not result in excess emissions. For deviations that result from breakdowns under District Rule 98, the permittee shall report the breakdown within two hours of detection of the breakdown and provide a follow-up written report after corrective actions have been taken. For deviations not due to a breakdown but which result in excess emissions, the permittee shall report the deviation within ten calendar days of detection. For all other deviations where no specific time frame for reporting a deviation applies, the permittee shall report the deviation at the time of the next semi-annual monitoring summary or annual compliance certification, whichever occurs first. If an underlying applicable requirement contains a definition of prompt or otherwise specifies a time frame for reporting deviations, then the criteria for the applicable requirement shall apply. The report must include the probable cause of such deviations and any corrective actions or preventive measures taken. [Rule 1421]

#### **D. GENERAL PERMIT REQUIREMENTS**

- The permittee shall comply with all terms and conditions of this permit. This permit consists of this document and Appendices A, B and C. Any noncompliance with the federally applicable terms and conditions of this permit shall constitute a violation of the federal Clean Air Act. Noncompliance with any federally applicable permit term or condition of this permit is grounds for federal enforcement action or enforcement action by the District; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. Noncompliance with any District permit term or condition is grounds for enforcement action by the District. [Rule 1421]
2. Upon a written request by the District, the permittee shall furnish to the District any information needed to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit; any information required to determine compliance with this permit; or any records required to be maintained pursuant to this permit. Such information shall be provided within a reasonable time, as specified within the District's written request. [Rule 1421]
  3. The permittee shall pay annual fees in accordance with District Rule 40. [Rule 1421]
  4. The permittee shall provide access, facilities, utilities and any necessary safety equipment for source testing and inspection upon request from the District. [Rule 19]
  5. This permit shall be maintained on-site at all times and be made available to the District upon request. [Rule 1410]
  6. The Rule Reference Table provided in Appendix B shall be used to determine whether a cited rule is a federally and District enforceable requirement or a District only enforceable requirement. Any new or revised District rule shall not be considered federally enforceable until the rule is approved by EPA into the SIP. In cases where

SIP approval is pending for a revised District rule, the rule citation shall refer to both the current SIP approved rule and the revised District rule. [Rule 1421]

## SECTION II. FACILITY-WIDE REQUIREMENTS

### A. GENERAL PERMIT PROGRAM APPLICABLE REQUIREMENTS

The permittee shall comply with the applicable requirements specified in the Rules and Regulations cited below, unless specifically exempted by the same Rule or Regulation.

Regulation	Rule Citation	Title
SDCAPCD Reg. II	10	Permits Required
SDCAPCD Reg. II	19	Provision of Sampling & Testing Facilities
SDCAPCD Reg. II	19.3	Emission Information
SDCAPCD Reg. II	20, 20.1, 20.2, 20.3	New Source Review (NSR)
SDCAPCD Reg. II	21	Permit Conditions
SDCAPCD Reg. II	24	Temporary Permit to Operate
SDCAPCD Reg. II	25	Appeals
SDCAPCD Reg. IV	60	Circumvention
SDCAPCD Reg. V	98	Breakdown Conditions: Emergency Variance
SDCAPCD Reg. VI	101	Burning Control

### B. FACILITY-WIDE/OTHER PROHIBITORY & MISC. REQUIREMENTS

The permittee shall comply with the generally applicable requirements specified in the Rules and Regulations cited below, unless specifically exempted by the same Rule or Regulation. These generally applicable requirements apply on a facility-wide basis to all permitted equipment, registered equipment, and insignificant activities. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more permitted emission units, the requirement is also included in Section III.A. of this permit.

Regulation	Rule Citation	Title
SDCAPCD Reg. IV	50	Visible Emissions
SDCAPCD Reg. IV	51	Nuisance
SDCAPCD Reg. IV	52	Particulate Matter
SDCAPCD Reg. IV	54	Dust and Fumes
SDCAPCD Reg. IV	67.0.1	Architectural Coatings
SDCAPCD Reg. IV	67.17	Storage of Materials Containing VOC
SDCAPCD Reg. IV	71	Abrasive Blasting
SDCAPCD Reg. XII	1200*	Toxic Air Contaminants – New Source Review
SDCAPCD Reg. XII	1206**	Asbestos Removal, Renovation, and Demolition
40 CFR Part 60	Subpart A	NSPS General Provisions
40 CFR Part 63	Subpart A	NESHAP General Provisions
40 CFR Part 82	Subpart A	Production and Consumption Controls
40 CFR Part 82	Subpart B	Servicing of Motor Vehicle Air Conditioners
40 CFR Part 82	Subpart F	Recycling and Emissions Reduction

\*Not Federally Enforceable

\*\* The District issued its own Asbestos Rule 1206 intended to be as stringent as Subpart M. The facility is subject to the most stringent requirements of either rule, which at the time of this report is ensured by compliance with Rule 1206.

**C. PERMIT SHIELDS**

1. No permit shield applies.

**D. ADDITIONAL TERMS**

1. Any emission unit described in this Title V operating permit as being fired on natural gas, shall only use Public Utility Commission (PUC)-quality natural gas, unless the emission unit permit specifies otherwise. [Rules 53, 62]
2. The permittee shall comply with all applicable requirements, including but not limited to, those applicable requirements of 40 CFR Parts 60 and 63.

**SECTION III EMISSION UNIT REQUIREMENTS**

**A. DISTRICT PERMITTED EMISSION UNITS**

Facility Emission Units (EU) are listed below and attached in Appendix A, including all terms and conditions of such permits, and comprise the emission unit portion of this Title V Operating Permit.

EU Reference	Source
APCD2008-PTO-971111	Active Landfill

**B. REGISTERED AND LEASED EMISSION UNITS**

The permittee shall comply with the source specific applicable requirements specified in the rules and regulations cited below for all registered emission units, unless specifically exempted by the same rule or regulations.

Regulation	Rule Citation	Title
SDCAPCD Reg. IV	52	Particulate Matter
SDCAPCD Reg. IV	53	Specific Contaminants
SDCAPCD Reg. IV	54	Dust and Fumes
SDCAPCD Reg. IV	62	Sulfur Content of Fuels
SDCAPCD Reg. IV	67.6	Solvent Cleaning Operations
SDCAPCD Reg. IV	69.4	Stationary Reciprocating Internal Combustion Engines

**C. INSIGNIFICANT EMISSION UNITS AND ACTIVITIES**



The permittee shall comply with all applicable requirements for any Insignificant Units located at this facility that are listed at District Regulation XIV, Appendix-A. Insignificant Units at this facility include the following:

- Stationary organic compound storage tanks excluding tanks subject to Rule 61.9) with a capacity of  $\leq 250$  gallons.

[Regulation XIV, App A, Section (e)(1)]

#### **D. ENGINES SUBJECT TO THE FEDERAL NESHAP**

1. The permittee is subject to 40 CFR 63 Subpart ZZZZ – *National Emission Standards for Hazardous Air Pollutants (NESHAP) for Stationary Reciprocating Internal Combustion Engines (RICE)*. For each stationary RICE with a power rating less than 50 brake horsepower, the permittee must perform the following maintenance:

- a. Change engine oil and filter every 500 hours of operation or annually, whichever comes first; or test the oil in accordance with 40 CFR § 63.6625(i);
- b. Inspect the air cleaner of a compression ignition engine or inspect spark plugs of a spark ignition engine, every 1,000 hours of operation or annually, whichever comes first, and replace as necessary;
- c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.

[40 CFR 63 Subpart ZZZZ § 63.6603(a) and Table 2d]

2. The permittee must keep records of the maintenance conducted on the stationary RICE in order to demonstrate compliance. [40 CFR 63 Subpart ZZZZ § 63.6655(e)]

3. For any stationary RICE with a power rating equal to or greater than 50 brake horsepower, the permittee must apply for a District permit in accordance with District Rule 10.

[Rules 10 & 11]

### **SECTION III DISTRICT-ONLY PROVISIONS**

#### **VARIANCE PROCEDURES**

The permittee may seek relief from District enforcement action from District-only provisions in the event of a breakdown in accordance with District Rule 98. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance does not provide relief from federal enforcement or citizen's suits.

[Rule 98]

**SECTION V. APPENDICES**

**APPENDIX A: DISTRICT PERMITS**

<b>Permit Number</b>	<b>Source Category</b>
APCD2008-PTO-971111	Active Landfill

**COUNTY OF SAN DIEGO, AIR POLLUTION CONTROL DISTRICT**  
10124 OLD GROVE ROAD, SAN DIEGO, CA 92131  
(858) 586-2600 FAX (858) 586-2601

PERMIT NO.  
APCD2008-PTO-971111

**PERMIT TO OPERATE**

The following is hereby granted a Permit To Operate the article, machine, equipment or contrivance described below. This permit is not transferable to a new owner nor is it valid for operation of the equipment at another location except as specified. This Permit To Operate or copy must be posted on or within 25 feet of the equipment, or readily available on the operating premises.

Sycamore Landfill Inc.  
Jordy Bjorkman  
8514 Mast Blvd.  
Santee, CA 92071

EQUIPMENT ADDRESS  
Sycamore Landfill Inc.  
8514 Mast Blvd.  
Santee, CA 92071

**EQUIPMENT DESCRIPTION**

An active non-hazardous waste landfill operation that includes quarrying, municipal waste disposal, waste compaction, cover material application, haul road activities, and a landfill gas monitoring, collection, and flare system consisting of: Landfill Gas (LFG) collection wells with associated fittings, piping and individual well shut off valves; offsite LFG migration probes with associated fittings and sampling ports; 4 LFG blowers with associated fittings, valves and piping; flame arrestor; liquid knockout vessel; 59 MM BTU/hr enclosed ground flare (approximately 8 ft dia x 30 ft high) and a 54 MM Btu/hr enclosed ground flare (approximately 8 ft dia x 40 ft high) equipped with optical flame detectors, automatic shut off valves and auxiliary fuel. The flares are equipped with condensate injection atomizing gun, stack temperature probes, in-line LFG oxygen analyzers, and LFG flow meters at flare station.

Every person who owns or operates this equipment is required to comply with the conditions listed below and all applicable requirements and District rules, including but not limited to Rules 10, 20, 40, 50, and 51.

**DISTRICT- AND FEDERALLY-ENFORCEABLE CONDITIONS**

1. The Permittee shall comply with all current and future applicable requirements of District Rule 59, District Rule 59.1, 40 CFR 60 Subpart XXX and 40 CFR 63 Subpart AAAA, including but not limited to the requirements listed in this permit, such as compliance provisions, monitoring of operations, specifications for active control systems, and recording keeping requirements.
  - (a) Permittee shall implement the compliance provisions in accordance with 40 CFR Subpart AAAA, 63.1960.
  - (b) Permittee shall implement the monitoring of operations in accordance with 40 CFR Subpart AAAA, 63.1961.
  - (c) Permittee shall implement the specifications for active collection systems in accordance with 40 CFR Subpart AAAA, 63.1962.

(d) Permittee shall implement the reporting requirements in accordance with 40 CFR Subpart AAAA, 63.1981.

(e) Permittee shall maintain records in accordance with 40 CFR Subpart AAAA, 63.1983.

2. Permittee shall operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require the Permittee to make any further efforts to reduce emissions if the requirements of this subpart have been achieved. Determination of whether a source is operating in compliance with operation and maintenance requirements will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[40 CFR Subpart AAAA, 63.1955]

3. The collection and control system may be capped, removed, or decommissioned if the following criteria are met:

(a) The landfill is a closed landfill (as defined in 40 CFR Subpart AAAA, 63.1990). A closure report must be submitted to the Administrator as provided in 40 CFR Subpart AAAA, 63.1981(f);

(b) The gas collection and control system has been in operation a minimum of 15 years or the Permittee demonstrates that the gas collection and control system will be unable to operate for 15 years due to declining gas flow; and

(c) Following the procedures specified in 40 CFR Subpart AAAA, 63.1959(c), the calculated NMOC emission rate at the landfill is less than 50 Mg/yr on three successive test dates. The test dates must be no less than 90 days apart, and no more than 180 days apart.

[40 CFR Subpart AAAA, 63.1957(b)]

4. Permittee shall operate the collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for:

(a) 5 years or more if active; or

(b) 2 years or more if closed or at final grade;

[40 CFR Subpart AAAA, 63.1958(a)]

5. Permittee shall operate the collection system with negative pressure at each wellhead except under the following conditions:

(a) A fire or increased well temperature. Permittee shall record instances when positive pressure occurs in efforts to avoid a fire. These records must be submitted with the semi-annual reports as provided in 40 CFR Subpart AAAA, 63.1981(h);

(b) Use of a geomembrane or synthetic cover. Permittee shall develop acceptable pressure limits in the design plan;

(c) A decommissioned well. A well may experience a static positive pressure after shut down to accommodate for declining flows. All design changes must be approved by the Administrator as specified in 40 CFR Subpart AAAA, 63.1981(d)(2);

[40 CFR Subpart AAAA, 63.1958(b)]

6. Permittee shall operate each interior wellhead in the collection system with a landfill gas temperature less than 62.8 degrees Celsius (145 degrees Fahrenheit). Permittee may establish

a higher operating temperature value at a particular well. A higher operating value demonstration must be submitted to the Administrator for approval and must include supporting data demonstrating that the elevated parameter neither causes fires nor significantly inhibits anaerobic decomposition by killing methanogens. The demonstration must satisfy both criteria in order to be approved (i.e., neither causing fires nor killing methanogens is acceptable).

[40 CFR Subpart AAAA, 63.1958(c)]

7. Permittee shall operate the collection system so that the methane concentration is less than 500 parts per million (ppm) above background at the surface of the landfill. To determine if this level is exceeded, the Permittee shall conduct surface testing around the perimeter of the collection area and along a pattern that traverses the landfill at no more than 30-meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover. The Permittee may establish an alternative traversing pattern that ensures equivalent coverage. A surface monitoring design plan must be developed that includes a topographical map with the monitoring route and the rationale for any site-specific deviations from the 30-meter intervals. Areas with steep slopes or other dangerous areas may be excluded from the surface testing.

[40 CFR Subpart AAAA, 63.1958(d)(1)]

8. Permittee shall:

- (a) Conduct surface testing using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in 40 CFR Subpart AAAA, 63.1960(d).

- (b) Conduct surface testing at all cover penetrations. Thus, the Permittee shall monitor any cover penetrations that are within an area of the landfill where waste has been placed and a gas collection system is required.

- (c) Determine the latitude and longitude coordinates of each exceedance using an instrument with an accuracy of at least 4 meters. The coordinates must be in decimal degrees with at least five decimal places.

[40 CFR Subpart AAAA, 63.1958(d)(2)]

9. Permittee shall operate the system in accordance to 40 CFR Subpart AAAA, 63.1955(c) such that all collected gases are vented to a control system designed and operated in compliance with 40 CFR Subpart AAAA, 63.1959(b)(2)(iii).

[40 CFR Subpart AAAA, 63.1958(e)(1)]

10. In the event the collection or control system is not operating:

- (a) The gas mover system must be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere must be closed within 1 hour of the collection or control system not operating; and

- (b) Efforts to repair the collection or control system must be initiated and completed in a manner such that downtime is kept to a minimum, and the collection and control system must be returned to operation.

[40 CFR Subpart AAAA, 63.1958(e)(1)]

11. Permittee shall operate the control system at all times when the collected gas is routed to the system.

[40 CFR Subpart AAAA, 63.1958(f)]

12. If monitoring demonstrates that the operational requirements in Conditions 5, 6, 7, and 8 of this Permit are not met, corrective action must be taken as specified in 40 CFR Subpart AAAA, 63.1960(a)(3) and (5) or (c). If corrective actions are taken as specified in 40 CFR Subpart AAAA, 63.1960, the monitored exceedance is not a deviation of the operational requirements in this section.

[40 CFR Subpart AAAA, 63.1958(g)]

13. Three-hour block averages used to demonstrate compliance shall be calculated according to 40 CFR Subpart AAAA, 63.1983(b)(2)(i) and 63.1983(c)(1)(i) and the data collected during the events listed below shall be included in any average computed under 40 CFR Subpart AAAA (Sections 63.1930-1990):

(a) Monitoring system breakdowns, repairs, calibration checks, and zero (low-level) and high-level adjustments.

(b) Startups.

(c) Shutdowns.

(d) Malfunctions.

[40 CFR Subpart AAAA, 63.1975]

14. The permittee shall operate, adjust and maintain the gas collection system to prevent excessive quantities of air from being drawn into the landfill. An oxygen analyzer designed to be accurate to +/- 0.5% by volume shall be installed in the collection piping at the flare station, maintained in good working condition and calibrated at least biennially. The concentration of oxygen in landfill gas at the flare station shall not exceed 3.5% by volume oxygen analyzer calibration records shall be maintained for at least five years and made available to the District upon request.

[Rules 21 and 59.1]

15. The permittee shall route all the collected landfill gas to the landfill gas destruction system.

[Rule 59.1; 17 CCR 95464(b)(1)(A)]

16. The landfill gas destruction system shall be operated to reduce non-methane organic compounds (NMOC) by 98% by weight or reduce the NMOC outlet concentration to less than 20 ppmv on a dry basis as hexane at 3 percent oxygen.

[Rule 59.1]

17. The permittee shall monitor the flare exhaust gas temperature. The gas temperature monitoring device shall be equipped with a continuous recorder which has an accuracy of +/- 1 percent of the temperature being measured.

[Rule 59.1; 17 CCR 95969(b)(1)(A)]

18. A thermocouple designed to be accurate to +/- 50° F at 1500° F shall be installed in the flare stack and maintained in good working condition. The temperature of the exhaust gas in the flare stack shall be displayed at the flare station during incineration.

[Rules 21 and 59.1]

19. The permittee shall monitor and record gas flow from the collection system to the flare at least once every 15 minutes.

[Rule 59.1; 17 CCR 95969(b)(1)(B)]

20. The system shall be continuously monitored for the presence of a flare flame.

[Rules 21 and 59.1]

21. In the event that the gas collection system or the gas combustion device is inoperable, the gas mover system shall be shut down and all valves in the collection system and gas combustion device contributing to venting of the gas to the atmosphere shall be closed within 1 hour or the landfill gas vented to the flare. This Provision does not apply to the gas combustion device during periods of start-up, shutdown, or malfunction provided the duration of start-up, shutdown, or malfunction does not exceed 1 hour.

[Rule 59.1]

22. The flow rate of landfill gas into each flare shall not exceed 1800 scfm. A meter shall be installed at the flare station which measures and displays the landfill gas flow rate. Permittee shall calibrate this meter at least biennially.

[Rules 21 and 59.1]

23. A shut-off valve shall be in place and maintained at each well head.

[Rules 21 and 59.1]

24. Except for a flare ignition and startup not to exceed 15 minutes, permittee shall ensure complete combustion of landfill gases during operation by maintaining the stack gas exit temperature at no less than 1500° F or as otherwise specified by the flare manufacturer, averaged over any 15 minute period. Supplemental fuel (natural gas or propane) shall be added as necessary to maintain the required stack gas exit temperature.

[Rule 20.3(d)(1)]

25. An automatic shutoff device shall stop the flow of landfill gas to the flare whenever conditions of flame-out, excessive exhaust gas temperature (>1800° F), or excessive landfill gas oxygen content (>3.5% by volume) occur.

[Rules 21 and 59.1]

26. There shall be no leaks of landfill gas from the collection system and flare equipment in excess of 1375 ppmv (measured as methane) at a distance of 1/2 inch from the transfer path other than non-repeatable, momentary readings. This Requirement does not apply during active maintenance, repair or sampling activities.

[Rules 21 and 59.1(d)(2)(ii)]

27. The equipment shall be properly maintained in good operating condition at all times. Calibration and maintenance records required by this permit shall be retained for at least five (5) years and be made available to the District on request.

[17 CCR 95470(a)]

28. The Permittee shall inspect each off-site gas migration probe with a combustible gas indicator for the presence of methane on a minimum quarterly basis and retain records. Inspection records shall be made available to the District on request.

[Rule 21]

29. Should the District, San Diego County Health Department or any health agency of the state of California determine that an imminent, life endangering threat to human life requiring immediate action exists on-site, the permittee shall take whatever actions are deemed necessary by the District and/or the health agency to protect human health.

[California Health and Safety Code Section 25358.3]

30. Emissions of sulfur compounds from this emission unit, calculated as sulfur dioxide, shall not exceed 0.05% by volume on a dry basis.

[Rule 53]

31. Emissions of combustion particulates shall not exceed 0.10 grains per dry standard cubic foot of gas standardized to 12 percent carbon dioxide by volume.

[Rule 53]

32. If requested by the District or EPA, emissions of sulfur compounds and/or combustion particulates shall be measured in accordance with EPA Reference Methods or equivalent methods as approved by the District.

[Rule 21]

33. Visible emissions from any part of the landfill shall not exceed Number 1 designation on the Ringelmann Chart (equivalent to 20% opacity) for a period or periods aggregating more than three minutes in any 60 consecutive minutes.

[Rule 50]

34. There shall be no leachate or condensate from any part of the landfill which reaches any surface and results in the discharge of toxic air contaminants or non-methane organic compounds to the atmosphere.

[Rules 21 and 59.1]

35. The active waste disposal operation shall not exceed the maximum elevation 883 ft above mean sea level and area size of 520 acres limits specified in the Integrated Waste Management Board Permit Number 37-AA-0023. These limits are equivalent to a design capacity of approximately 43,655,000 cubic yards or 34,640,240 ton capacity.

[Rule 21]

36. Access, facilities, utilities and any necessary safety equipment for source testing and inspection shall be provided upon request of the Air Pollution Control District.

[Rule 19]

## **DISTRICT-ONLY-ENFORCEABLE CONDITIONS**

37. At no time shall the subject equipment cause or contribute to a public nuisance as specified in District Rule 51. If compliance with Rule 51 cannot be demonstrated to the satisfaction of the District, the permittee will take whatever corrective action necessary to meet applicable requirements. If corrective action requires any physical change or modification to the subject equipment the permittee shall apply for and obtain an Authority to Construct for all such modifications prior to making any physical change.

[Rule 51]

38. This Air Pollution Control District permit does not relieve the holder from obtaining permits or authorizations required by other governmental agencies.

39. The permittee shall, upon determination of applicability and written notification by the District, comply with all applicable requirements of the air toxics "Hot Spots" Information and Assessment Act.



[California Health and Safety Code Section 44300 et seq.]

40. The permittee is subject to Title 17 California Code of Regulations (CCR) SUBARTICLE 6. METHANE EMISSIONS FROM MUNICIPAL SOLID WASTE LANDFILLS (17 CCR §§ 95460 – 95476 and Appendix I), which includes, but may not be limited to, the requirements cited in this permit.

[17 CCR § 95461]

41. The permittee shall operate the gas collection and control system in accordance with 17 CCR section 95464(b), which includes, but is not limited to, the following:

- a. Route the collected gas to a gas control device or devices except as provided in 17 CCR sections 95464(d) - well raising, and 95464(e) - Repairs and Temporary Shutdown of Gas Collection System Components;
- b. So that there is no landfill gas leak that exceeds 500 ppmv, measured as methane, at any component under positive pressure. Measurement for this determination shall be made at a distance of one half of an inch or less for a component source that exceeds 500 parts per million by volume (ppmv), excluding non-repeatable, momentary readings; measurement of leaks from any vault must be taken within 3 inches above the surface of the vault exposed to the atmosphere. [17 CCR § 95464(b)(1)(B) and the definition of component leak at § 95475];
- c. So that all the landfill gas is drawn toward the gas control device or devices;
- d. So that each wellhead remains under vacuum (negative pressure), except under the following conditions:
  - i. Use of a geomembrane or synthetic cover, provided permittee establishes acceptable pressure limits for the wellheads and includes them in the Design Plan;
  - ii. A decommissioned well;
  - iii. Well raising activities in which new fill is being added or compacted in the immediate vicinity around the well, or a well extension that, once installed, is sealed or capped until the raised well is reconnected to a vacuum source.

[17 CCR §§ 95464(b)(1), 95464(c) and 95464(d)]

42. Except as provided in sections 95464(d), 95464(e), and 95466, no location on the landfill surface may exceed either of the following concentrations of methane:

- a. 500 ppmv, other than non-repeatable, momentary readings, as determined by instantaneous surface emissions monitoring, measured at a distance of 3 inches above surface as required by § 95471(c)(1)(A).
- b. An average of 25 ppmv as determined by integrated surface emissions monitoring.

[17 CCR § 95465]

43. The requirements of section 95465 do not apply to the working face of the landfill or to areas of the landfill surface where the landfill cover material has been removed and refuse has been exposed for the purpose of installing, expanding, replacing, or repairing components of the landfill gas, leachate, or gas condensate collection and removal system, or for law enforcement activities requiring excavation.

[17 CCR § 95466]

44. If the permittee operates a flare for the control of landfill gas, the flare must meet the following requirements:
- a. Achieves a methane destruction efficiency of at least 99 percent by weight;
  - b. Is equipped with automatic dampers, an automatic shutdown device, a flame arrester, and continuous recording temperature sensors;
  - c. During startup or restart there must be sufficient flow of propane or commercial natural gas to the burners to prevent unburned collected methane from being emitted to the atmosphere;
  - d. The gas control device must be operated within the parameter ranges established during the initial or most recent source test.

[17 CCR § 95464(b)(2)(A)]

45. If the Permittee operates a landfill gas control device other than a flare, the device must meet the following requirements:
- a. Achieves a methane destruction efficiency of at least 99 percent by weight. Lean burn internal combustion engines must reduce the outlet methane concentration to less than 3,000 ppmv, dry basis, corrected to 15 percent oxygen.
  - b. If a boiler or a process heater is used as the gas control device, the landfill gas stream must be introduced into the flame zone. Where the landfill gas is not the primary fuel for the boiler or process heater, introduction of the landfill gas stream into the flame zone is not required.
  - c. The gas control device must be operated within the parameter ranges established during the initial or most recent source test.
46. The permittee must conduct an annual source test for flare control efficiency using the test methods identified in 17 CCR 95471(f). Each succeeding complete annual source test must be conducted no later than 45 days after the anniversary date of the initial source test.

If a gas control device remains in compliance after three consecutive source tests the permittee may conduct the source test every three years. If a subsequent source test shows the gas collection and control system is out of compliance the source testing frequency will return to annual.

[17 CCR § 95464(b)(4)]

47. The requirements of 17 CCR sections 95464(b)(1)(A), 95464(b)(1)(B), and 95464(c) do not apply to individual landfill gas collection system components that must be temporarily shut down in order to repair the components, due to catastrophic events such as earthquakes, to connect new landfill gas collection system components to the existing system, to extinguish landfill fires, or to perform construction activities pursuant to section 95466, provided the following requirements are met:
- a. Any new gas collection system components required to maintain compliance with 17 CCR 95464 must be included in the most recent Design Plan pursuant to section 95464(a)(4);
  - b. Methane emissions must be minimized during shutdown pursuant to section 95464(a)(1)(D).

[17 CCR § 95464(e)(1-2)]

48. 54. The permittee must monitor each individual wellhead monthly to determine the gauge pressure. If there is any positive pressure reading other than as provided in 17 CCR sections 95464(d) and 95464(e), the permittee must take the following actions:

- a. Initiate corrective action within five calendar days of the positive pressure measurement;
- b. If the problem cannot be corrected within 15 days of the date the positive pressure was first measured, the Permittee must initiate further action, including, but not limited to, any necessary expansion of the gas collection system, to mitigate any positive pressure readings;
- c. Corrective actions, including any expansion of the gas collection and control system, must be completed and any new wells must be operating within 120 days of the date the positive pressure was first measured, or it is a violation.

[17 CCR § 95469(c)]

49. Components containing landfill gas that are under positive pressure must be monitored quarterly for leaks. Any component leak must be tagged and repaired within 10 calendar days, or it is a violation.

[17 CCR § 95469(b)(3)]

50. Component leak testing at MSW landfills having landfill gas-to-energy facilities may be conducted prior to scheduled maintenance or planned outage periods.

[17 CCR § 95469(b)(3)(A)]

51. The permittee must conduct quarterly surface monitoring in accordance with 17 CCR section 95469 using the equipment and procedures specified in section 95471. Instantaneous surface monitoring shall be conducted using either an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications given at 17 CCR § 95471(a) and using the applicable procedures given at 17 CCR § 95471(c) including, but not limited to, the monitoring grid layout.

[17 CCR § 95469(a)]

52. Instantaneous Surface Monitoring under 17 CCR SUBARTICLE 6: Pursuant to section 95465(a)(1), any landfill surface reading exceeding 500 ppmv, other than non-repeatable, momentary readings, as determined by instantaneous surface emissions monitoring, must be recorded as an exceedance and the following actions taken:

- a. The Permittee must record the date, location, and value of each exceedance, along with re-test dates and results. The location of each exceedance must be clearly marked and identified on a topographic map of the MSW landfill, drawn to scale with the location of both the grids and the gas collection system clearly identified.
- b. Corrective action must be taken by the Permittee such as, but not limited to, cover maintenance or repair, or well vacuum adjustments and the location must be re-monitored within ten calendar days of a measured exceedance.
  - i. If the re-monitoring of the location shows a second exceedance, additional corrective action must be taken and the location must be re-monitored again no later than 10 calendar days after the second exceedance.
  - ii. If the re-monitoring shows a third exceedance, the Permittee must install a new or replacement well, unless an alternative solution is identified and approved by the District, as determined to achieve compliance no later than 120 calendar days after detecting the third exceedance, or it is a violation of this subarticle.
- c. Any closed or inactive MSW landfill, or any closed or inactive areas on an active MSW landfill that has no monitored exceedances of the 500 ppmv methane limit specified in section 95465(a)(1) after four consecutive quarterly monitoring periods may monitor

annually. Any exceedances of this limit detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring of the landfill.

- d. Any exceedances of the 500 ppmv methane limit specified in section 95465(a)(1) detected during any compliance inspections will result in a return to quarterly monitoring of the landfill.
- e. Any instantaneous methane measurement of 200 ppmv or greater must be recorded as a reportable reading pursuant to 17 CCR 95971(a)(1)(D).

[17 CCR §§ 95969(a)(2) and 95971]

53. Integrated Surface Monitoring under 17 CCR SUBARTICLE 6: Any reading exceeding an average of 25 ppmv as specified in 17 CCR section 95465(a)(2) must be recorded as an exceedance and the following actions must be taken:

- a. The permittee must record the average surface concentration measured as methane for each grid along with re-test dates and results. The location of the grids and the gas collection system must be clearly marked and identified on a topographic map of the MSW landfill drawn to scale.
- b. Within 10 calendar days of a measured exceedance, corrective action must be taken by the permittee such as, but not limited to, cover maintenance or repair, or well vacuum adjustments and the grid must be re-monitored.
  - i. If the re-monitoring of the grid shows a second exceedance, additional corrective action must be taken and the location must be re-monitored again no later than 10 calendar days after the second exceedance.
  - ii. If the re-monitoring in section 95469(a)(2)(B)1. shows a third exceedance, the permittee must install a new or replacement well as determined to achieve compliance no later than 120 calendar days after detecting the third exceedance, or it is a violation of this subarticle.
- c. Any closed or inactive MSW landfill, or any closed or inactive areas on an active MSW landfill that has no monitored exceedances of the limit specified in section 95465(a)(2) after 4 consecutive quarterly monitoring periods may monitor annually. Any exceedances of the limits specified in section 95465(a)(2) detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring of the landfill.
- d. Any exceedances of the limits specified in section 95465(a)(2) detected during any compliance inspections will result in a return to quarterly monitoring of the landfill.

[17 CCR § 95969(a)(2)]

54. The Permittee of a closed or inactive MSW landfill, or any closed or inactive area on an active MSW landfill, that can demonstrate that in the three years before the effective date of this subarticle that there were no measured exceedances of the limits specified in section 95465 by annual or quarterly monitoring may monitor annually. Any exceedances of the surface methane emission limits specified in section 95465 detected during the annual monitoring that cannot be remediated within 10 calendar days will result in a return to quarterly monitoring.

[17 CCR § 95469(a)(3)]

55. Component Monitoring under 17 CCR SUBARTICLE 6: Components containing landfill gas and under positive pressure must be monitored quarterly for leaks. Any component leak must

be tagged and repaired within 10 calendar days, or it is a violation. Component leak testing at MSW landfills having landfill gas-to-energy facilities may be conducted prior to scheduled maintenance or planned outage periods.

[17 CCR § 95969(b)(3)]

56. Alternate compliance options: The Permittee may request alternatives to the compliance measures, monitoring requirements, test methods and procedures of sections 95464, 95469, and 95471. Any alternatives requested by the Permittee must be submitted in writing to the Control Officer of the Air Pollution Control District, San Diego County. Alternative compliance option requests may include, but are not limited to, the following:

- a. Semi-continuous operation of the gas collection and control system due to insufficient landfill gas flow rates.
- b. Additional time allowance for leak repairs for landfills having consistent issues related to the procurement and delivery of necessary parts to complete the repair, or adverse weather conditions that impede repair work.
- c. Alternative wind speed requirements for landfills consistently having winds in excess of the limits specified in this subarticle.
- d. Alternative walking patterns to address potential safety and other issues, such as: steep or slippery slopes, monitoring instrument obstructions, and physical obstructions.
- e. Exclusion of construction areas and other dangerous areas from landfill surface inspection.
- f. Exclusion of paved roads that do not have any cracks, pot holes, or other penetrations from landfill surface inspection. [17 CCR § 95468(a)]

57. *Recordkeeping – five-year retention*, 17 CCR SUBARTICLE 6: In addition to any other records required by this permit, the permittee must maintain the following records for at least five (5) years:

- a. All gas collection system downtime exceeding five calendar days, including individual well shutdown and disconnection times, and the reason for the downtime.
- b. All gas control system downtime in excess of one hour, the reason for the downtime, and the length of time the gas control system was shutdown.
- c. Expected gas generation flow rate calculated pursuant to section 95471(e) – 2006 Intergovernmental Panel on Climate Change (IPCC) Guidelines for National Greenhouse Gas Inventories, Chapter 3, using a recovery rate of 75%.
- d. Records of all instantaneous surface readings of 200 ppmv or greater; all exceedances of the limits in sections 95464(b)(1)(B) or 95465, including the location of the leak (or affected grid), leak concentration in ppmv, date and time of measurement, the action taken to repair the leak, date of repair, any required re-monitoring and the re-monitored concentration in ppmv, and wind speed during surface sampling; and the installation date and location of each well installed as part of a gas collection system expansion.
- e. Records of any positive wellhead gauge pressure measurements, the date of the measurements, the well identification number, and the corrective action taken.
- f. Annual solid waste acceptance rate and the current amount of waste-in-place.
- g. Records of the nature, location, amount, and date of deposition of non-degradable waste for any landfill areas excluded from the collection system.
- h. Results of any source tests conducted pursuant to section 95464(b)(4).

- i. Records describing the mitigation measures taken to prevent the release of methane or other emissions into the atmosphere:
  - i. When solid waste was brought to the surface during the installation or preparation of wells, piping, or other equipment;
  - ii. During repairs or the temporary shutdown of gas collection system components;
  - iii. When solid waste was excavated and moved.
- j. Records of any construction activities pursuant to section 95466. The records must contain the following information:
  - i. A description of the actions being taken, the areas of the MSW landfill that will be affected by these actions, the reason the actions are required, and any landfill gas collection system components that will be affected by these actions.
  - ii. Construction start and finish dates, projected equipment installation dates, and projected shut down times for individual gas collection system components.
  - iii. A description of the mitigation measures taken to minimize methane emissions and other potential air quality impacts.
- k. Records of the equipment operating parameters specified to be monitored under sections 95469(b)(1) and 95469(b)(2) as well as records for periods of operation during which the parameter boundaries established during the most recent source test are exceeded. The records must include the following information:
  - i. For enclosed flares, all 3-hour periods of operation during which the average temperature difference was more than 28 degrees Celsius (or 50 degrees Fahrenheit) below the average combustion temperature during the most recent source test at which compliance with sections 95464(b)(2) and 95464(b)(3)(A) was determined.
  - ii. For boilers or process heaters, whenever there is a change in the location at which the vent stream is introduced into the flame zone pursuant to section 95464(b)(3)(A)2.
  - iii. For any permittee who uses a boiler or process heater with a design heat input capacity of 44 megawatts (150 MMBtu/hr) or greater to comply with section 95464(b)(3), all periods of operation of the boiler or process heater (e.g., steam use, fuel use, or monitoring data collected pursuant to other federal, State, local, or tribal regulatory requirements).

[17 CCR § 95470(a)(1)]

58. *Recordkeeping – retention for life of control device*, 17 CCR SUBARTICLE 6: Permittee must maintain the following records for the life of each gas control device:

- a. The control device vendor specifications.
- b. The expected gas generation flow rate as calculated pursuant to section 95471(e).
- c. The percent reduction of methane achieved by the control device determined pursuant to section 95471(f).
- d. For a boiler or process heater, the description of the location at which the collected gas vent stream is introduced into the boiler or process heater over the same time period of the performance test.
- e. For an open flare: the flare type (i.e., steam-assisted, air-assisted, or non-assisted); all visible emission readings, heat content determination, flow rate or bypass flow rate measurements, and exit velocity determinations made during the performance test as

specified in 40 CFR § 60.18 (as last amended 73 Fed. Reg. 78209 (December 22, 2008), which is incorporated by reference herein; and records of the flare pilot flame or flare flame monitoring and records of all periods of operations during which the pilot flame or the flare flame is absent.

[17 CCR § 95470(a)(2)]

59. *Record Storage*: The permittee must maintain copies of the records and reports required by this subarticle and provide them to the District within five business days upon request. Records and reports must be kept at a location within the State of California.

[17 CCR § 95470(a)(3)]

60. *Annual Report*: Except as given in 17 CCR section 95463, permittee must prepare an annual report for the period of January 1 through December 31 of each year. Each annual report must be submitted to the District by March 15 of the following year and must contain the following information:

- a. MSW landfill name, permittee, address, and solid waste information system (SWIS) identification number.
- b. Total volume of landfill gas collected (reported in standard cubic feet).
- c. Average composition of the landfill gas collected over the reporting period (reported in percent methane and percent carbon dioxide by volume).
- d. Gas control device type, year of installation, rating, fuel type, and total amount of landfill gas combusted in each control device.
- e. The date that the gas collection and control system was installed and in full operation.
- f. The percent methane destruction efficiency of each gas control device(s).
- g. Type and amount of supplemental fuels burned with the landfill gas in each device.
- h. Total volume of landfill gas shipped off-site, the composition of the landfill gas collected (reported in percent methane and percent carbon dioxide by volume), and the recipient of the gas.
- i. Most recent topographic map of the site showing the areas with final cover and a geomembrane and the areas with final cover without a geomembrane with corresponding percentages over the landfill surface.
- j. The information records cited herein and required by sections 95470(a)(1)(A), 95470(a)(1)(B), 95470(a)(1)(C), 95470(a)(1)(D), 95470(a)(1)(E), and 95470(a)(1)(F), 95470(a)(1)(H), and 95470(a)(1)(K).

[17 CCR § 95470(b)(3)]

61. *Waste-in-Place Report*: If the MSW landfill contains less than 450,000 tons of waste-in-place, or the landfill contains 450,000 tons or more of waste-in-place and landfill gas recovery reaches or exceeds 3.0 MMBtu/hr, as given by section 95463(a) or section 95643(b)(2)(B)3., permittee must report the following information to the District:

- a. MSW landfill name, permittee, address, and solid waste information system (SWIS) identification number.
- b. The landfill's status (active, closed, or inactive) and the estimated waste-in-place, in tons.

- c. Most recent topographic map of the site showing the areas with final cover and a geomembrane and the areas with final cover without a geomembrane with corresponding percentages over the landfill surface.

[17 CCR § 95470(b)(4)]

62. *Landfill Gas Heat Input Capacity Report*: Permittee must calculate the landfill gas heat input capacity as required by section 95463(b) (i.e., gas heat input capacity report requirement for landfills greater than or equal to 450,000 tons of waste-in-place) using the procedures specified in section 95471(b) (i.e., procedure as specified in Appendix I, as applicable) and report the results to the District within 90 days of the effective date of this subarticle or upon reaching 450,000 tons of waste-in-place. The calculation, along with relevant parameters, must be provided as part of the report.

[17 CCR § 95470(b)(5)]

63. Any report, or information submitted pursuant to 17 CCR subarticle 6 must contain certification by a responsible official of truth, accuracy, and completeness. This certification, and any other certification required under this subarticle, must state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

[17 CCR § 95470(b)(6)]

64. Each part of 17 CCR Subarticle 6 is deemed severable, and in the event that any part of this subarticle is held to be invalid, the remainder of this subarticle continues in full force and effect.

[17 CCR § 95476]



## APPENDIX B: RULE REFERENCE TABLE

Rule Citation <sup>1</sup>	RULE TITLE	A/R <sup>2</sup>	District Adoption Date <sup>3</sup>	SIP FR Approval Date
	<b>REGULATION I - GENERAL PROVISIONS</b>			
1	Title	F	04/30/80	09/28/81
2	Definitions	F	11/04/09	09/17/10
4	Review of Rules	F	01/01/70†	09/22/72
5	Authority to Arrest	F	03/24/76†	05/11/77
	<b>REGULATION II - PERMITS</b>			
10	Permits Required	F	07/25/95	03/11/98
10.1††	NSPS & NESHAPS Requirements	D	11/8/76	N/A
11	Exemptions from Rule 10 Permit Requirements	D/F	09/20/78	07/06/82
12	Registration of Specified Equipment	D	11/15/00	N/A
12.1	Portable Equipment Registration	D	05/21/97	N/A
14	Applications	F	04/30/80	09/28/81
15	Permit Process - Public Notifications	D/F	09/18/90	Pending
17	Cancellation of Applications	F	04/06/93	03/11/98
18	Action on Applications	F	01/17/72	09/22/72
18	Action on Applications	D/F	09/18/90	Pending
19	Provision of Sampling and Testing Facilities	F	04/06/93	03/11/98
19.1††	NSPS & NESHAPS Provision of Sampling and Testing Facilities Requirements	D	11/08/76	N/A
19.2	Continuous Emission Monitoring Requirements	F	01/12/79	09/28/81
19.3	Emission Information	F	5/15/96	03/09/00
20	Standards for Granting Permits	F	04/25/89	10/04/18
20.1	NSR - General Provisions	F	04/27/16	10/04/18
20.2	NSR - Non-major Stationary Sources	F	04/27/16	10/04/18
20.3	NSR - Major Stationary Source and PSD Stationary Source	F	04/27/16	10/04/18
20.4	NSR - Portable Emission Units	F	04/27/16	10/04/18
20.5	Power Plants	F	07/05/79	04/14/81
20.6	Standards for Permit to Operate - Air Quality Analysis	F	04/27/16	10/04/18
20.8	Special Offset Requirement Relating to Banking	D	2/16/83	N/A
21	Permit Conditions	F	11/29/94	03/11/98
22	Denial of Applications	D/F	01/01/69†	N/A
23	Further Information	D/F	01/01/69†	N/A
24	Temporary Permit to Operate	F	03/20/96	10/24/08
25	Appeals	F	01/01/69†	09/22/72
25	Appeals	D/F	06/21/00	Pending
26.0	Banking of Emission Reduction Credits (ERCs) - General Requirements	D/F	10/22/97	Pending
26.1	Standards for Granting Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending

26.2	Use of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.3	Reclassification of Class B Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.4	Permanency of Banked Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.5	Transfer of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.6	District Banking of Emission Reduction Credits (ERCs)	D/F	10/22/97	Pending
26.7	Shutdown and Related Emission Unit	D/F	10/22/97	Pending
26.8	Banking of Limited Emission Reductions	D/F	10/22/97	Pending
26.9	Emission Reduction Credit Certificates and The Emission Reduction Credit Register	D/F	10/22/97	Pending
26.10	Banking For BRAC Military Base Closure or Realignment Actions	D/F	10/22/97	Pending
27	Banking of Mobile Source Emission Reduction Credits	D/F	11/29/94	Pending
27.1	Federal Requirements for San Diego County APCD Alternative Mobile Source Emission Reduction Program Approved On 9/8/2000	F	08/06/08	06/03/09
	<b>REGULATIONS III - FEES</b>			
40	Permit Fees	D	01/01/12	N/A
42	Hearing Board Fees	D	07/01/00	N/A
44	Technical Reports, Charges for	D	12/7/83	N/A
	<b>REGULATIONS IV - PROHIBITIONS</b>			
50	Visible Emissions	F	08/13/97	12/7/98
50.1††	NSPS & NESHAPS Visible Emissions Requirements	D	11/08/76	N/A
51	Nuisance	F	01/01/69†	09/22/72
52	Particulate Matter	F	01/22/97	12/9/98
52.1††	NSPS & NESHAPS Particular Matter Requirements	D	11/08/76	N/A
53	Specific Contaminants	F	01/22/97	12/9/98
53.1	Scavenger Plants	F	01/01/69†	09/22/72
53.2††	NSPS & NESHAPS Specific Contaminants Requirements	D	11/08/76	N/A
54	Dusts and Fumes	F	01/22/97	12/9/98
54.1	NSPS & NESHAP Dust and Fumes Requirement	D	11/08/76	N/A
58	Incinerator Burning	F	01/17/73†	05/11/77
59	Control of Waste Disposal - Site Emissions	D	11/03/87	N/A
59.1	Municipal Solid Waste Landfills	D	06/17/98	N/A
60	Circumvention	F	05/17/94	03/09/00
60.2	Limiting Potential to Emit - Synthetic Minor Sources	D	04/04/12	N/A
61.0	Definitions Pertaining to the Storage & Handling of Organic Compounds	F	10/16/90	09/13/93
61.1	Receiving & Storing Volatile Organic Compounds at Bulk Plants & Bulk Terminals	F	01/10/95	08/08/95
61.2	Transfer of Volatile Organic Compounds into Mobile Transport Tanks	F	07/26/00	08/26/03
61.3	Transfer of Volatile Organic Compounds into Stationary Storage Tanks	F	10/16/90	06/30/93
61.3.1	Transfer of Gasoline into Stationary Underground Storage Tanks	D	03/01/06	Pending

61.4	Transfer of Volatile Organic Compounds into Vehicle Fuel Tanks	F	10/16/90	05/13/93
61.4	Transfer of Volatile Organic Compounds into Vehicle Fuel Tanks	D/F	03/26/08	Pending
61.4.1	Transfer of Gasoline from Stationary Underground Storage Tanks into Vehicles Fuel Tanks	D	03/01/06	N/A
61.5	Visible Emission Standards for Vapor Control Systems	F	09/20/78 <sup>†</sup>	04/14/81
61.6	NSPS Requirements for Storage of Volatile Organic Compounds	D	01/13/87	Withdrawn
61.7	Spillage and Leakage of Volatile Organic Compounds	F	01/13/87	03/11/98
61.8	Certification Requirements for Vapor Control Equipment	F	01/13/87	03/11/98
62	Sulfur Content of Fuels	F	10/21/81	07/06/82
62.1 <sup>††</sup>	NSPS Requirements for Sulfur Content of Fuels	D	11/08/76	N/A
64	Reduction of Animal Matter	F	08/21/81	07/06/82
66	Organic Solvents	F	07/25/95	Repealed
66.1	Miscellaneous Surface Coating Operations and Other Processes Emitting VOCs	D/F	2/24/10	08/09/12
67.0.1	Architectural Coatings	F	06/24/15	11/13/15
67.1	Alternative Emission Control Plans	F	05/15/96	03/27/97
67.2	Dry Cleaning Equipment Using Petroleum - Based Solvent	F	05/15/96	03/27/97
67.3	Metal Parts and Products Coating Operations	F	04/09/03	11/14/03
67.4	Metal Container, Metal Closure and Metal Coil Coating Operations	F	11/09/11	09/20/12
67.5	Paper, Film and Fabric Coating Operations	F	05/15/96	03/27/97
67.6.1	Cold Solvent Cleaning and Stripping Operations	F	5/23/07	10/13/09
67.6.2	Vapor Degreasing Operations	F	5/23/07	10/13/09
67.7	Cutback and Emulsified Asphalts	F	05/15/96	03/27/97
67.9	Aerospace Coating Operations	F	04/30/97	08/17/98
67.10	Kelp Processing and Bio-Polymer Manufacturing	F	06/25/97	06/22/98
67.11	Wood Parts and Products Coating Operations	F	06/27/12	04/11/13
67.12.1	Polyester Resin Operations	F	05/11/16	04/02/18
67.15	Pharmaceutical and Cosmetic Manufacturing Operations	F	05/15/96	03/27/97
67.16	Graphic Arts Operations	F	05/09/12	09/20/12
67.17	Storage of Materials Containing Volatile Organic Compounds	F	05/15/96	03/27/97
67.18	Marine Coating Operations	F	05/15/96	03/27/97
67.19	Coating and Printing Inks Manufacturing Operations	F	05/15/96	05/26/00
67.20.1	Motor Vehicle and Mobile Equipment Coating Operations	D	06/30/10	N/A
67.21	Adhesive Material Application Operations	D	11/14/08	N/A
67.22	Expandable Polystyrene Foam Products Manufacturing Operations	D	05/15/96	N/A
67.24	Bakery Ovens	F	05/15/96	03/27/97
68	Fuel-Burning Equipment – Oxides of Nitrogen	F	09/20/94	04/09/96
68.1 <sup>††</sup>	NSPS Requirements for Oxides of Nitrogen from Fuel-Burning Equipment	D	11/08/76	N/A

69	Electrical Generating Steam Boilers, Replacement Units & New Units	D	12/12/95	N/A
69.2	Industrial & Commercial Boilers, Process Heaters & Steam Generators	F	09/27/94	02/09/96
69.2.1	Small Boilers, Process Heaters and Steam Generators	D/F	03/25/09	Pending
69.2.2	Medium Boilers, Process Heaters and Steam Generators	D/F	07/08/20	Pending
69.3	Stationary Gas Turbine Engines	F	09/27/94	06/17/97
69.3	Stationary Gas Turbine Engines – RACT	D/F	12/16/98	Pending
69.3.1	Stationary Gas Turbine Engines – BARCT	D	02/24/10	N/A
69.4	Stationary Internal Combustion Engines	F	07/30/03	01/04/06
69.4	Stationary Internal Combustion Engines – RACT (withdrawal pending EPA approval of 69.4.1)	D/F	07/30/03	2/25/04 (Withdrawal Pending)
69.4.1	Stationary Internal Combustion Engines - BARCT	D/F	11/15/00	Pending
69.5	Natural Gas-Fired Water Heaters	D	01/01/99	N/A
69.5.1	Natural Gas-Fired Water Heaters	D	06/24/15	N/A
69.6	Natural Gas-Fired Fan-Type Central Furnaces	D	06/17/98	N/A
70	Orchard Heaters	F	01/17/72	09/22/72
71	Abrasive Blasting	F	03/30/77	08/31/78
	<b>REGULATION V - PROCEDURES BEFORE THE HEARING BOARD</b>			
75	Procedure Before the Hearing Board	D/F	09/17/85	Pending
75.1††	NSPS & NESHAPS Variance Procedures	D	09/17/85	7/30/79
97	Emergency Variance	D/F	07/25/95	Pending
98	Breakdown Conditions: Emergency Variance	D	07/25/95	Withdrawn
	<b>REGULATION VI - BURNING CONTROL</b>			
101	Burning Control	F	09/25/02	04/30/03
	<b>REGULATION VII - VALIDITY AND EFFECTIVE DATE</b>			
140	Validity	F	01/01/69†	09/22/72
141	Effective Date	F	01/01/69†	09/22/72
	<b>REGULATION VIII - SAN DIEGO AIR POLLUTION EMERGENCY PLAN</b>			
126	Applicability	F	05/25/77	08/31/78
127	Episode Criteria Levels	F	09/17/91	03/18/99
128	Episode Declaration	F	09/17/91	03/18/99
129	Episode Termination	F	05/25/77	08/31/78
130	Episode Actions	F	09/17/91	03/18/99
131	Stationary Source Curtailment Plan	F	04/01/81	06/21/82
132	Traffic Abatement Plan	F	04/01/81	06/21/82
132	Traffic Abatement Plan	D/F	12/17/97	Pending
133	Schools	F	05/25/77	08/31/78
134	Source Inspection	F	04/01/81	06/21/82

135	Air Monitoring Stations	F	05/25/77	08/31/78
136	Interdistrict and Interbasin Coordination	F	05/25/77	08/31/78
137	Emergency Action Committee	F	05/25/77	08/31/78
138	Procedures and Plans	F	05/25/77	08/31/78
	APPENDIX A - Persons to be Notified on Episode Declaration	F		
<b>REGULATION IX - PUBLIC RECORDS</b>				
175	General	F	05/22/74†	05/11/77
176	Information Supplied to District	F	05/22/74†	05/11/77
177	Inspection of Public Records	F	03/30/77	08/31/78
177	Inspection of Public Records	D/F	06/20/01	Pending
<b>REGULATION XII - TOXIC AIR CONTAMINANTS</b>				
1200	Toxic Air Contaminants - New Source Review	D	06/12/96	N/A
1202	Hexavalent Chromium - Cooling Towers	D	07/25/95	N/A
1203	Ethylene Oxide Sterilizers and Aerators	D	07/26/00	N/A
1205	Control of Dioxins Emissions from Medical Waste Incinerators	D	01/01/94	N/A
1210	Toxic Air Contaminant Public Health Risks - Public Notification and Risk Reduction	D	06/12/96	N/A

<b>REGULATION XIV - TITLE V OPERATING PERMITS</b>				
1401	General Provisions	F	02/27/04	02/27/04
1410	Permit Required	F	02/27/04	02/27/04
1411	Exemption from Permit to Operate for Insignificant Units	F	03/07/95	11/30/01
1412	Federal Acid Rain Program Requirements	F	01/18/94	11/30/01
1413	Early Reduction of Hazardous Air Pollutants	F	03/07/95	11/30/01
1414	Applications	F	03/07/95	11/30/01
1415	Permit Process-Public Notification	F	02/27/04	02/27/04
1417	Pendency & Cancellation of Applications	F	03/07/95	11/30/01
1418	Action on Applications	F	02/27/04	11/30/01
1419	Provisions of Sampling & Testing Facilities & Emission Information	F	03/07/95	11/30/01
1420	Standards for Granting Permits	F	03/07/95	11/30/01
1421	Permit Conditions	F	02/27/04	02/27/04
1422	Denial or Cancellation Of Applications	F	03/07/95	11/30/01
1423	Further Information	F	01/18/94	11/30/01
1424	Applications Deemed Denied	F	01/18/94	11/30/01
1425	Appeals & Judicial Review	F	02/27/04	02/27/04
	APPENDIX A - Insignificant Units	F	02/27/04	11/30/01
<b>REGULATION XV - FEDERAL CONFORMITY</b>				
1501	Conformity of General Federal Actions	F	06/22/99	04/23/99

The following NSPS and NESHAP have been adopted locally by the District. EPA has granted the District delegation for each of these rules. Therefore, these rules, as adopted by the District are the federally applicable requirements. For all other NSPS and NESHAP, the versions cited in the CFR are the federally applicable requirements.

<b>Subpart &amp; Citation</b>	<b>RULE TITLE</b>	<b>District Adoption Date(s)</b>	<b>Federal Delegation Date</b>
<b>Part 60</b>	<b>REGULATION X - STANDARDS OF PERFORMANCE FOR NEW STATIONARY SOURCES</b>		
A	General Provisions	Unknown 11/03/92	11/08/76
E	Standards of Performance for Incinerators	Unknown	03/30/77
I	Standards of Performance for Asphalt Concrete Plants	Unknown 01/13/87	11/08/76
J	Standards of Performance for Petroleum Refineries	Unknown	11/08/76
L	Standards of Performance for Secondary Lead Smelters	Unknown	11/08/76
M	Standards of Performance for Secondary Brass and Bronze Ingot Production Plants	Unknown 09/17/85	03/30/77
O	Standards of Performance for Sewage Treatment Plants	01/13/87	09/17/87
DD	Standards of Performance for Grain Elevators	Unknown	05/24/82
EE	Standards of Performance for Surface Coating Metal Furniture	03/04/86 11/03/92	03/19/87
QQ	Standards of Performance for the Graphic Arts Industry: Publication Rotogravure Printing	08/24/83	12/22/83
RR	Standards of Performance for Pressure Sensitive Tape and Label Surface Coating Operations	09/17/86 11/03/92	03/19/87
SS	Standards of Performance for the Industrial Surface Coating Large Appliances	02/22/84 11/03/92	04/24/84
TT	Standards of Performance for Metal Coil Surface Coating	02/22/84 11/03/92	04/24/84
BBB	Standards of Performance for the Rubber Tire Manufacturing Industry	03/14/89	07/18/89
FFF	Standards of Performance for Flexible Vinyl and Urethane Coating and Printing	09/17/86	03/19/87
JJJ	Standards of Performance for Petroleum Dry Cleaners	12/15/87	07/18/89
<b>Part 61</b>	<b>REGULATION XI- NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAPS)</b>		
A	General Provisions	01/13/87	05/24/82
C	National Emission Standard for Beryllium	Unknown	11/08/76
D	National Emission Standard for Beryllium Rocket Motor Firing	Unknown	11/08/76
E	National Emission Standard for Mercury	03/27/90	05/17/91
F	National Emission Standard for Vinyl Chloride	08/17/77 06/16/78	11/21/77

The following ATCM and NESHAP have not been adopted by the District, but are being implemented and enforced by the District as ATCM's.

<b>Subpart &amp; Citation</b>	<b>RULE TITLE</b>	<b>A/R</b>	<b>Most Recent Adoption Date</b>
<b>DISTRICT RULES AND REGULATIONS APPENDIX A - CALIFORNIA AIRBORNE TOXIC CONTROL MEASURES (ATCM)</b>			
17 CCR § 93102	Hexavalent Chromium ATCM for Chrome Plating & Chromic Acid Anodizing Operations	D/F	12/7/06
17 CCR § 93109	ATCM For Emissions of Perchloroethylene From Dry Cleaning Operations	F	01/25/07
17 CCR § 93101.5	ATCM to Reduce Emissions of Hexavalent Chromium and Nickel from Thermal Spraying	D	09/30/05
17 CCR § 93105	ATCM for Construction, Grading, Quarrying, and Surface Mining Operations	D	07/26/01
17 CCR § 93106	Asbestos ATCM for Surface Applications	D	07/20/00
17 CCR § 93107	ATCM For Emissions of Toxic Metals From Non-Ferrous Metal Melting	D	01/14/93
17 CCR § 93111	ATCM for Emissions of Chlorinated Toxic Air Contaminants from Automotive Maintenance & Repair Activities	D	04/27/00
17 CCR § 93112	ATCM for Emissions of Hexavalent Chromium and Cadmium from Motor Vehicle and Motor Equipment Coatings	D	09/20/01
17 CCR § 93113	ATCM to Reduce Emissions of Toxic Air Contaminants from Outdoor Residential Waste Burning	D	02/03/03
17 CCR § 93115	ATCM for Stationary Compression Ignition Engines	D	05/19/11
17 CCR § 93116	ATCM for Portable Diesel-Fueled Engines	D	02/19/11
<b>DISTRICT RULES AND REGULATIONS APPENDIX B - NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAP) FOR SOURCE CATEGORIES</b>			
<b>Part 63</b>			
A	General Provisions	F	05/16/07
N	Hard and Decorative Chromium Electroplating and Chromium Anodizing Tanks	F	04/20/06
O	Ethylene Oxide Sterilization Facilities	F	12/28/07
R	Gasoline Distribution	F	01/24/11
T	Halogenated Solvent Cleaning	F	09/08/00
DD	Off-site Waste & Recovery Operations	F	07/20/99
GG	Aerospace Manufacturing and Rework Facilities	F	12/08/00
II	Shipbuilding and Ship Repair (Surface Coating)	F	12/15/95
JJ	Wood Furniture Manufacturing Operations	F	12/28/98
VVV	Publicly Owned Treatment Works	F	10/21/02
AAAA	Municipal Solid Waste Landfills	F	03/26/20
EEEE	Organic Liquids Distribution (non-gasoline)	F	07/17/08
MMMM	Surface Coating of Miscellaneous Metal Parts and Products	F	04/26/04
PPPP	Plastic Parts (surface coating)	F	04/24/07
SSSS	Surface Coating of Metal Coil	F	03/17/03
VVVV	Boat Manufacturing	F	08/22/01
WWWW	Reinforced Plastic Composites Production	F	8/25/05



YYYY	Stationary Combustion Turbines	F	08/18/04
ZZZZ	Stationary Reciprocating Internal Combustion Engines	F	03/09/11
DDDDD	Industrial, Commercial, and Institutional Boilers and Process Heaters	F	05/18/11
GGGGG	Site Remediation	F	11/29/06
HHHHH	Miscellaneous Coating Manufacturing	F	10/04/06
PPPPP	Engine Test Cells/Stands	F	08/28/03
WWWWW	Hospital Ethylene Oxide Sterilizers Area Sources	F	12/28/07
BBBBBB	Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities	F	01/24/11
CCCCC	Gasoline Dispensing Facilities	F	01/24/11
HHHHHH	Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources	F	01/09/08
JJJJJ	Area Sources: Industrial, Commercial, and Institutional Boilers	F	3/21/11
QQQQQ	Wood Preserving Area Sources	F	07/16/07
VVVVV	Chemical Manufacturing Area Sources	F	11/29/09
WWWWW	Plating and Polishing Operations Area Sources	F	07/01/08
XXXXXX	Metal Fabrication and Finishing Area Sources	F	7/23/08
AAAAAAA	Asphalt Processing and Asphalt Roofing Manufacturing Area Sources	F	12/02/09
CCCCCCC	Paint and Allied Products Manufacture Area Sources	F	12/03/09

The following NSPS have been adopted by the District by reference. The rules listed below are the CFR versions of these rules which are federally applicable requirements.

<b>Subpart &amp; Citation</b>	<b>RULE TITLE</b>	<b>Latest EPA Promulgation Date</b>	<b>District Adoption Date</b>	<b>Delegation Date</b>
<b>Part 60</b>	<b>DISTRICT RULES AND REGULATIONS APPENDIX C - STANDARDS OF PERFORMANCE FOR NEW STATIONARY SOURCES (NSPS)</b>			
D	Standards of Performance for Fossil-Fuel-Fired Steam Generators for Which Construction is Commenced After August 17, 1971	10/17/00 01/28/09	10/17/01 06/24/09	01/03/08 Pending
Da	Standards of Performance for Electric Utility Steam Generating Units for Which Construction is Commenced After September 18, 1978	06/11/01 01/28/09	10/17/01 06/24/09	01/03/08 Pending
Db	Standards of Performance for Industrial-Commercial - Institutional Steam Generating Units	10/01/01 01/28/09	04/25/01 06/24/09	01/03/08 Pending
Dc	Standards of Performance for Small Industrial-Commercial -Institutional Steam Generating Units	05/08/96 01/28/09	08/13/97 06/24/09	06/24/98 Pending
GG	Standards of Performance for Stationary Gas Turbines	06/27/89 02/24/06	10/17/01 02/25/09	01/03/08 Pending
K	Standards of Performance for Storage Vessels for Petroleum Liquids Construct After June 11, 1973 and Prior to May 19, 1978	10/17/00	06/20/07	01/03/08
Ka	Standards of Performance for Storage Vessels for Petroleum Liquids Construction after May 18, 1978	12/14/00	06/20/07	01/03/08
Kb	Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984	10/15/03	06/20/07	01/03/08
AAA	Standards of Performance for New Residential Wood Heaters	06/12/99 10/17/00	04/12/00 N/A	01/03/08 N/A
OOO	Standards of Performance for Nonmetallic Mineral Processing Plants	06/09/97 10/17/00	04/28/99 N/A	05/28/02 N/A
UUU	Standards of Performance for Calciners and Dryers in Mineral Industries	07/29/93 10/17/00	11/17/99 N/A	05/28/02 N/A
VVV	Standards for Polymeric Coating of Supporting Substrates Facilities	09/11/89	05/23/07	01/03/08
WWW	Standards of Performance for Municipal Solid Waste Landfills	04/10/00	08/13/97	06/24/98
XXX	Standards of Performance for Municipal Solid Waste Landfills That Commenced Construction, Reconstruction, or Modification After July 17, 2014	08/29/2016	N/A	N/A
AAAA	Standards of Performance for Small Municipal Waste Combustion Units	12/06/00	06/20/07	01/03/08
CCCC	Standards of Performance for Commercial and Industrial Solid Waste Incineration Units	12/01/00	06/20/07	01/03/08
EEEE	Standards of Performance for Other Solid Waste Incineration Units	12/16/05	06/20/07	01/03/08
KKKK	Standards of Performance for Stationary Combustion Turbines	07/06/06	02/25/09	06/01/09

The following NSPS have not been adopted by the District and are not delegated to the District. However, the District has the authority to enforce the NSPS through the Title V program. The rules listed below are the CFR versions of these rules, which are federally applicable requirements.

<b>Subpart &amp; Citation</b>	<b>RULE TITLE</b>	<b>Latest EPA Promulgation Date</b>	<b>District Adoption Date</b>	<b>Delegation Date</b>
<b>Part 60</b>				
III	Standards of Performance for Stationary Compression Ignition Internal Combustion Engines	07/11/06	N/A	N/A
JJJ	Standards of Performance for Stationary Spark Ignition Internal Combustion Engines	01/18/08	N/A	N/A

1. Rule Citations marked with an “††” contain no substantive requirements and are listed for informational purposes only.
2. ‘A/R’ Denotes enforceability of the listed applicable requirement as follows:
  - ‘F’ Denotes a Federal applicable requirement that is federally enforceable and District enforceable.
  - ‘D/F’ Denotes a District applicable requirement which is pending SIP approval. When such a rule receives SIP approval, it supersedes the existing SIP rule and becomes the Federal applicable requirement.
  - ‘D’ Denotes a District only applicable requirement. This may include some state requirements that are enforceable by the District.
3. District adoption dates marked with an “†” are the effective date of the rule, the actual adoption date is uncertain.
4. On September 17, 2010, EPA approved the District’s November, 4, 2009, revision to the table of exempt compounds in Rule 2, which can be administratively amended without Board action to amend the rule.

## APPENDIX C: ABBREVIATIONS THAT MAY APPEAR IN THIS PERMIT

APCO	Air Pollution Control Officer
ASTM	American Society for Testing and Methods
BACT	Best Available Control Technology
CAA	federal Clean Air Act
CFR	Code of Federal Regulations
CO	Carbon Monoxide
CO <sub>2</sub>	Carbon Dioxide
District	San Diego County Air Pollution Control District
EF	Emission Factor
EPA	US Environmental Protection Agency
HAP	Hazardous Air Pollutant
I&M	Inspection and Maintenance
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
[NSR]	New Source Review based condition
NO <sub>x</sub>	Oxides of nitrogen
O <sub>2</sub>	Oxygen
OES	Office of Environmental Services
O&M	Operation and maintenance
Pb	Lead
PM	Total Particulate Matter
PM <sub>10</sub>	Particulate matter with aerodynamic equivalent diameter of ≤ 10 microns
PSD	Prevention of Significant Deterioration
RMP	Risk Management Plan
SDCAPCD	San Diego County Air Pollution Control District
SIP	State Implementation Plan
SO <sub>x</sub>	Oxides of sulfur
Title IV	Title IV of the federal Clean Air Act
Title V	Title V of the federal Clean Air Act
VOC	Volatile organic compound

### Units of Measure:

dscf	=	Dry standard cubic foot
g	=	grams
gal	=	gallon
gr/dscf	=	Grains per dry standard cubic foot
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
min	=	minute
MM Btu	=	Million British thermal units
psia	=	pounds per square inch, absolute
scf	=	Standard cubic foot
scfm	=	standard cubic feet per minute
yr	=	year